

Capella Gen2 Vapor Proof



CCT	3000K / 4000K / 5000K / 6500K
CRI	80
SDCM	3
UGR	<24
BEAM ANGLE	124°
IP RATING	66
LED LUMEN DEPRECIATION	L80B10 @ 50000Hrs
DRIVER LIFETIME SPECIFICATION	F10 – 100000Hrs
SURGE PROTECTION DRIVER	2Kva
RIPPLE	<5%
DIFFUSER MATERIAL	UV Stabilized Polycarbonate
HOUSING MATERIAL	Glass Fibre Reinforced UV Stabilized Polyester
GASKET	Polyurethane
CLIPS	Stainless Steel
OPERATING TEMPERATURE	-30 – 45°C
WARRANTY	5 Yrs

MODIFICATION	WATTAGE	EFFICIENCY	LUMEN PACKAGE
2Ft 250Ma	12W	138 Lumens/W	1656 Lumens
2Ft 350Ma	18W	131 Lumens/W	2358 Lumens
2Ft 500Ma	26W	121 Lumens/W	3146 Lumens
4Ft 250Ma	24W	138 Lumens/W	3312 Lumens
4Ft 350Ma	36W	131 Lumens/W	4716 Lumens
4Ft 500Ma	51W	125 Lumens/W	6375 Lumens
5Ft 250Ma	30W	138 Lumens/W	4140 Lumens
5Ft 350Ma	45W	131 Lumens/W	5895 Lumens
5Ft 500Ma	64W	121 Lumens/W	7744 Lumens

INDUSTRIAL