

Crater Stadium Floodlight



CCT	5000K
CRI	70
SDCM	3 / 5
BEAM ANGLES	30° / 60°
LED LIFETIME LUMEN DEPRECIATION	L80 @ 50000Hrs
DRIVER OPERATING TEMPERATURE	-40 – 90°C
LUMINAIRE OPERATING TEMPERATURE	-25 – 45°C
POWER FACTOR	0.9849
THD	<20%
SURGE PROTECTION DRIVER	4Kva
INLINE SURGE ARRESTOR AT DB BOARD / POLE	10Kva or 20Kva
DRIVER IP RATING	67
DRIVER RATING	62000Hrs
LUMINAIRE IP RATING	66
IMPACT RATING	IK10 +
WINDAGE	To be calculated based on entire pole design
HOUSING	Aluminum with Weather Resistant UV Stabilized Coating
SCREWS / CLIPS / FASTENERS	Stainless Steel
WARRANTY	10 Year Warranty

WATTAGE	EFFICIENCY	LUMEN PACKAGE
250W	130 Lumens/W	32500 Lumens
500W	130 Lumens/W	65000 Lumens
750W	130 Lumens/W	97500 Lumens
1000W	130 Lumens/W	130000 Lumens
1250W	130 Lumens/W	162500 Lumens