

Inground IP67 Kuma Linear Profile



SIZE	25 mm x 41 mm
MOUNTING OPTIONS	Inground
VOLTAGE	24V
WATTAGE / M	12 W/M
LED'S / M	120 LED / M
CCT	3000K /4000K
SDCM	3
HOUSING	AL6063 Weather Resistant Aluminium
HOUSING COLOURS	Standard Anodized / Black / White / Custom RAL
HOUSING IP RATING	IP67
DIFFUSER	UV Stabilized
DIFFUSER STAND WEIGHT MAX	30Kn
END CAPS	Weather Resistant Aluminium Fixed with Bolts
LED LIFETIME LUMEN DEPRECIATION	L80 B50 @ 50000Hrs
DRIVER LIFETIME SPECIFICATION	F10 – 100000Hrs
DIMMING METHODS	DALI / Triac / 1-10V /
EMERGENCY STANDBY TIMES	60Min / 120Min / 180Min
TOTAL WARRANTY	3 Yrs LED 5 Yrs Driver

LENGTH	WATTAGE	EFFICIENCY	LUMENS
1000 mm	12W	70 Lumens/W	840 Lumens
2000 mm	24W	70 Lumens/W	1680 Lumens
3000 mm	36W	70 Lumens/W	2520 Lumens