

LED Quasar



MOUNTING OPTIONS	Recessed Surfacemount
CCT	3000K / 4000K / 5000K / 6500K
SDCM	3
UGR	<16
HOUSING	0.8mm Cold Rolled Mild Steel Powder coated
PERFORATION OPTIONS	Single / Double / Triple / None
LOUVRE	Miro4 / Saturn
DIFFUSER	Brightview CHE85 or CHE95
LED LIFETIME LUMEN DEPRECIATION	L80 B10 @ 50000Hrs
DRIVER LIFETIME SPECIFICATION	F10 – 100000Hrs
DIMMING METHODS	DALI / Triac / 1-10V
EMERGENCY STANDBY TIMES	60Min / 120Min / 180Min
TOTAL WARRANTY	5Yrs

SIZE	LAMP CONFIGURATION	WATTAGE	EFFICIENCY	LUMENS
595 mm x 595 mm	2	28W	115 Lumens/W	3220
595 mm x 595 mm	2	36W	110 Lumens/W	3960
595 mm x 595 mm	2	51W	100 Lumens/W	5100
595 mm x 595 mm	3	42W	115 Lumens/W	4830
595 mm x 595 mm	3	54W	110 Lumens/W	5940
1195 mm x 595 mm	2	56W	115 Lumens/W	6440
1195 mm x 595 mm	2	72W	110 Lumens/W	7920
1195 mm x 595 mm	2	84W	103 Lumens/W	8652
1195 mm x 595 mm	3	84W	115 Lumens/W	9660
1195 mm x 595 mm	3	108W	110 Lumens/W	11880

4 LAMP QUASAR VARIATION ON REQUEST

C O M M E R C I A L R E C E S S E D