

## Vela Square Downlight



C O M M E R C I A L D O W N L I G H T S

<b>CCT</b>	3000K / 4000K / 5000K / 6500K
<b>CRI</b>	80 / 90
<b>SDCM</b>	3
<b>UGR</b>	<21
<b>BEAM ANGLES</b>	24° / 36° / 60°
<b>IP RATING</b>	20
<b>LED CHIP</b>	Citizen / Phillips
<b>LED LIFETIME LUMEN DEPRECIATION</b>	L80 @ 50000Hrs
<b>DRIVER LIFETIME SPECIFICATION</b>	50000Hrs
<b>TRIM COLOUR</b>	White / Black / Custom RAL
<b>DIMMING METHODS</b>	DALI / Triac / 1-10V
<b>EMERGENCY STANDBY TIMES</b>	60Min / 120Min
<b>TOTAL WARRANTY</b>	5 Yrs

CUT OUT	WATTAGE	EFFICIENCY	LUMENS
80mm x 80mm	10W	100 Lumens/W	1000 Lumens
105mm x 105mm	12W	100 Lumens/W	1200 Lumens
105mm x 105mm	15W	100 Lumens/W	1500 Lumens
105mm x 105mm	20W	100 Lumens/W	2000 Lumens
125mm x 125mm	25W	100 Lumens/W	2500 Lumens
125mm x 125mm	30W	100 Lumens/W	3000 Lumens

